

Table of Figures

Figure 1. K vs. Stiffness Ratio	3
Figure 2. Elastomeric Bearing Pad Stiffness Calculation.....	4
Figure 3. Model analyzed to obtain data shown in Figure 1.....	5
Figure 4. SAP Model to mimic Georgia Pier using NCDOT Point of Fixity,.....	10
Figure 5. Robeson County Bridge MultiPier Model from Robinson et al. (2006)	11
Figure 6. Robeson County Bridge SAP Model from Robinson et al. (2006)	12
Figure 7. Equivalent Model Parameters for Free (Longitudinal) and Fixed.....	14
Figure 8. Frame model of Northampton County Bridge using equivalent lengths.....	15
Figure 9. Rowan County bridge, under construction in 2005	24
Figure 10. MultiPier Model--Rowan County.....	26
Figure 11. Wake County Bridge R-2809D, 2006	29
Figure 12. Wake County Bridge MultiPier Model	32
Figure 13. Pitt County Bridge MultiPier Model	36
Figure 14. Boundary conditions for pile design (after AISC. LRFD Manual of Steel Construction, 2001).....	40
Figure 15. Bearing Pads provided by NCDOT.....	41
Figure 16. Example Lateral Loading Scheme.....	42
Figure 17. Experimental setup sketch (provided by Pablo Robalino) and test picture.....	43
Figure 18. Load cell and 60-ton jack	43
Figure 19. String Potentiometers	44
Figure 20. Linear Potentiometers.....	44
Figure 21. Closer view of the instrumentation.....	45
Figure 22. Force-displacement hysteretic response Type V-axial load 50 kips	46
Figure 23. Force-displacement hysteretic response for Type V-axial load 100 kips (444 kN)	47
Figure 24. Force-displacement hysteretic response for Type V-axial load 150 kips.....	48
Figure 25. Force-displacement hysteretic response for Type VI – 50 kips (222 kN).....	49
Figure 26. Force-displacement hysteretic response for Type VI – 100 kips (444 kN)....	50
Figure 27. Force-displacement hysteretic response for Type VI-150 kips (667 kN)	51
Figure 29. Nomenclature of the bearing pads test set up.....	53
Figure 30. Stress vs. shear strain relationship for Type V- 50 kips (222 kN)	54
Figure 31. Stress vs. shear strain relationship for Type V- 100 kips (444 kN)	55
Figure 32. Stress vs. shear strain relationship for Type V- 150 kips (667 kN)	56
Figure 33. Stress vs. shear strain relationship for Type VI- 50 kips (222 kN)	57
Figure 34. Stress vs. shear strain relationship for Type VI- 100 kips (444 kN)	58
Figure 35. Stress vs. shear strain relationship for Type VI- 150 kips (667 kN)	59
Figure 36. (a-b). Bearing pad shear deformations for 1 inch (25.4 mm) block displacement (Type V).....	63
Figure 37. (a-b) Bearing Pad deformations for 1.5" inch (38.1 mm) block displacement (Type V).....	63
Figure 38. (a-b) Bearing Pad deformations for 1 inch (25.4 mm) block displacement (Type VI)	64